

A-A-59166 Walkway Coating, Non-Slip, Type I & II

Technical Data Sheet (Page 1 of 2)

Description:

A nonslip walkway compound coating for use on walkways of exterior aircraft surfaces. Type I is smooth and can be applied by brushing or rolling, as well as spraying. Type II contains grit for additional non-skid properties and is for brushing and rolling application only.

Physical Properties:		
Colors:	Per Fed Std. 595B	
Type I:	Smooth Texture	
Type II:	Grit Added	
Finish:		
Lusterless Solids (Weight):	52 – 65%	
Tack Free:	15 Minutes	
Recoat:	30 Minutes	
Dry Through:	6 Hours	
Full Hardness:	24 Hours	
Full Cure:	7 Days	

Dhysical Droportios

Application Characteristics:

- (1) Non-Slip
- (2) Air Dry
- (3) Brush-able
- (4) Durable
- (5) Fast Dry

Typical Uses:

- (1) Exterior Aircraft Walkways
- (2) Heavy Traffic Areas
- (3) Non-Slip Requirements

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com www.superiorsalesdist.com



A-A-59166 Walkway Coating, Non-Slip, Type I & II

Technical Data Sheet (Page 2 of 2)

APPLICATION 7 REDUCTION:

Apply by brush or roll methods (or spray for Type I). Thin with MIL-T-81772B Type III Reducer or TT-X-916 Xylene as needed to facilitate proper flow. For Type II, do not over brush so that an even distribution of the grit is achieved.

SURFACE PREPARTAION:

Surface must be completely clean, structurally sound, and free of all contaminants (including dirt, wax, loose paint, grease, etc.). Do not paint over moist / wet surfaces.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.

USE WITH ADEQUATE VENTILATION.

AVOID CONTACT WITH SKIN AND EYES.

READ MATERIAL SAFETY DATA SHEET BEFORE USING.

CONTENTS ARE FLAMMABLE.